

CLAAS

AGRISHIFT BLS

80W-90

Lubricant specially developed for limited slip differentials of self-locking axles.

APPLICATIONS

Axles in agricultural tractors

- Lubrication of limited slip differentials of self-locking axles fitted in agricultural equipment.
- Developed for front axles, also suitable in certain rear axles.

PERFORMANCES

Classifications

API : GL-5-LS
MIL.L. : 2105D

Manufacturers approvals

ZF : TE-ML 05C / 12C / 21C

Meets manufacturers' specifications

FORD M2C 104A
STEYR...

CUSTOMER BENEFITS

Protection of the axle Devices

Driving comfort

- Eliminates vibrations and chatter in stressed self-blocking axles.
- Resists to extreme pressure
- Stable at high temperature
- Anti-rust and anti-corrosion properties
- Provides excellent protection against worm or stripped gear teeth under all operating conditions

CHARACTERISTICS

AGRISHIFT BLS	Units	80W-90
Kinematic viscosity at 40°C	mm ² /s	164
Kinematic viscosity at 100°C	mm ² /s	16,2
Viscosity index		102
Pour point	°C	-30

The typical characteristics mentioned represent mean values.

AGRISHIFT BLS 80W-90
Sheet updated : 06/2012
Sticker reference : FT 01-06

Developed with TOTAL
technology at the service of
CLAAS