

CLAAS

AGRIMOT ULTRATEC

10W-40

Very high performance lubricant for Diesel engines based upon a synthetic technology.

APPLICATIONS

Loaded Diesel engines Phases I, II or IIIa

- Particularly suitable for the lubrication of the latest generation Diesel engines developed by European manufacturers.
- New generation synthetic technology lubricant for all types of Diesel engines, turbo-charged or naturally aspirated, which are found on agricultural vehicles.
- Can handle the most severe applications.

PERFORMANCES

Classifications

ACEA : E4 / E7 / E5
API : CF

Manufacturers approvals

DAIMLER : MB-Approval 228.5
DEUTZ : DQC III-05

CUSTOMER BENEFITS

Security under loaded Conditions

Technical performances

- Recommended by all European engine manufacturers in case of severe working conditions.
- Easier cold start.
- Exceptional anti wear and detergency properties.
- Excellent service stability.
- Excellent dispersive, anti oxydant and anti corrosion properties.
- Exceptional performances due to the lubricant's synthetic basis added to high performance additives.

CHARACTERISTICS

AGRIMOT ULTRATEC	Units	10W-40
Kinematic viscosity at 40°C	mm ² /s	106
Kinematic viscosity at 100°C	mm ² /s	14,4
Viscosity index		139
Pour point	°C	-33

The typical characteristics mentioned represent mean values.

AGRIMOT ULTRATEC 10W-40
Sheet updated : 10/2008

Developed with TOTAL
technology at the service of
CLAAS